



Direct Illumination

LBRX 6 ROW SERIES – SMD High-density, rectangular illumination

- 6 Row SMD LED with lens arrays are arranged in rectangular array to provide rectangular illumination. The rectangular illumination can be mounted with different angle to provide difference in illumination reflection for image processing. Optional diffuser can be added to all LBRX series for more even light distribution.
- Application: general illumination, label inspection, character inspection, code recognition.

	<p>Technical specification:</p> <ul style="list-style-type: none"> - Color Red, Green, Blue and White - 24V DC Input Power - Continuous and Strobe Applications - Compact Size - Lighting Cable 500mm <p>Customize Lighting:</p> <ul style="list-style-type: none"> - Customize Sizes, Mounting requirements - Color and Voltage Available - Consult Technical Sales for More Information

MODEL	DIMENSION (MM)			COLOR	VOLTAGE/ WATT	CURRENT
	A	B	C			
LBRX-00-040-6-X	52.0	40.0	31.7	•••••	24V /1.87W 24V /1.73W	78mA 72mA
LBRX-00-080-6-X	92.0	80.0	31.7	•••••	24V /3.74W 24V /3.46W	156mA 144mA
LBRX-00-120-6-X	132.0	120.0	31.7	•••••	24V /5.62W 24V /5.18W	234mA 216mA
LBRX-00-160-6-X	172.0	160.0	31.7	•••••	24V /7.49W 24V /6.91W	312mA 288mA
LBRX-00-200-6-X	212.0	200.0	31.7	•••••	24V /9.36W 24V /8.64W	390mA 360mA